

Additional Accessories

Compact Flash

SanDisk Ultra Compact Flash cards have a minimum sustained write speed of 9 MB per second and a read speed of 30 MB per second.

Recommended for use with REAM HMI.



Cable Reel

For Use With: 50m of 1.5sqmm Cable Storage.



Serial Ports

ExpressCard providing one RS232 serial port. Up to 921,600 data transfer rates and the 128 byte deep transmit and 256 byte receive FIFOs, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop.



PC Card providing one RS232 serial port. Up to 921,600 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOs, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop.



Power Supply

AC to DC converter

Dimensions	168x78x44.5mm
Efficiency	80%
Input Voltage	90 ~ 264Vac
Line Regulation	1%
Load Regulation	5%
MTBF	>100,000 hrs
Number of Outputs	1
Operating Temperature	0 ~ +70°C
Output Current	3.33A
Output Voltage	24Vdc
Package	Desk Top
Power Rating	80W
Ripple And Noise	240mV
Type	Switch Mode
Weight	530g



DC to DC converter
100W DC-DC Converter
Input 12VDC (9-18V) DC
Output 24VDC 7A DC
Non Isolated

