



Description

- FREE, PLUG OR SOCKET, 4WAY & 6WAY
- Connector Type: Circular Military
- Series: MS3106A
- Connector Body Material: Aluminium Alloy
- Gender: Plug or socket
- Connector Mounting Orientation: Cable
- Connector Shell Size: 14S
- Insert Arrangement: 14S-2
- Contact Termination: Solder
- Contact Material: Copper Alloy
- Contact Plating: Silver
- Approval Bodies: MIL-C-5015
- Colour: Olive
- Connector Insert Type: 14S-2
- Connector Type: Circular
- Contact Material: Copper Alloy
- Contact Plating: Silver
- Contact Style: Pin
- Current Rating: 13A
- IP Rating: IP66
- Insulator Material: Neoprene
- Length: 38.18mm
- Material: Aluminium alloy
- Max Cable Diameter: 1.4mm
- Max Operating Temperature: 125°C
- Max Wire Size AWG: 22AWG
- Min Cable Diameter: 0.8mm
- Min Temperature Operating: -55°C
- Min Wire Size AWG: 16AWG
- Mounting Type: Cable
- Termination Method: Solder Bucket
- Voltage Rating AC: 250V
- Coupling Diameter: 28.52mm
- Dielectric Strength, VAC: 2800V
- Voltage Rating DC: 700V