



#### Description

- FREE, SOCKET OR PLUG, 2WAY & 3WAY
- Connector Type: Circular
- Series: 97
- Connector Body Material: Aluminium alloy
- Gender: Plug or socket
- Connector Mounting Orientation: Cable
- Connector Shell Size: 10SL
- Insert Arrangement: 10SL-4
- Contact Termination: Solder Bucket
- Contact Material: Copper Alloy
- Contact Plating: Silver
- Approval Bodies: MIL-C-5015, CSA
- Approval Category: UL Recognised
- Colour: Olive
- Connector Insert Type: 10SL-4
- Connector Type: Circular
- Contact Material: Copper Alloy
- Contact Plating: Silver
- Contact Style: Socket
- Current Rating: 13A
- Insulator Material: Neoprene
- Material: Aluminium alloy
- Max Cable Diameter: 1.4mm
- Max Operating Temperature: 125°C
- Max Wire Size AWG: 22AWG
- Min Cable Diameter: 0.8mm
- Min Temperature Operating: -55°C
- Min Wire Size AWG: 16AWG
- Mounting Type: Cable
- Termination Method: Solder Bucket
- Voltage Rating AC: 700V
- Working Voltage: 700V
- Dielectric Strength, VAC: 2800V
- Voltage Rating DC: 700V